

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:
A61B 5/03, A63B 23/20
A1
(11) International Publication Number: WO 97/10746
(43) International Publication Date: 27 March 1997 (27.03.97)

(21) International Application Number: PCT/GB96/02296

(22) International Filing Date: 20 September 1996 (20.09.96)

(30) Priority Data: 9519194.6 20 September 1995 (20.09.95) GB

(71) Applicant (for all designated States except US): UNIVERSITY
OF WALES COLLEGE OF MEDICINE [GB/GB]; Heath
Park, Cardiff CF4 4XN (GB).

(72) Inventors; and
(75) Inventors/Applicants (for US only): YOUNG, Howard, Leslie [GB/GB]; 56 Cheriton Drive, Thornhill, Cardiff CF4 5DF (GB). LOWNDES, Richard, Herbert [GB/GB]; Pelvic Floor and G.I. Physiology Unit, West Norwich Hospital, Bowthorpe Road, Norwich NR2 3TU (GB).

(74) Agents: NEWELL, William, Joseph; Wynne-Jones, Laine & James, 22 Rodney Road, Cheltenham, Gloucestershire GL50 1JJ (GB) et al.


(81) Designated States: AU, CA, GB, JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: ANORECTAL ANGLE MEASUREMENT



(57) Abstract

Apparatus (10) for measuring the anorectal angle comprises an outer rubber-like sheath (12), which may be a suitably modified catheter, within which is disposed an elongate angular deflection detector (14) which provides on display (16) a read-out of the angular deflection of the apparatus. The sheath (12) may include pressure ports with associated pressure lines back to the proximal end of the sheath to allow the pressure to be read at different points along the anal canal.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
UA	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	I E	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	, RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	· SG	Singapore
CH	Switzerland	KZ	Kazakhstan	Si	Slovenia
CI	Côte d'Ivoire	u	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD .	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Larvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

WO 97/10746 PCT/GB96/02296

ANORECTAL ANGLE MEASUREMENT

This invention relates to apparatus and methods for measuring the anorectal angle and more generally to apparatus and methods for measuring, monitoring or observing the local anatomy or selected parameters in the anal canal and/or rectum.

5

10

15

Measurement of the anorectal angle (the angle of the anus relative to the rectum) is part of the investigations undertaken to determine the functionality of the anal canal and rectum in patients suffering defecatory disorders. The passage of stools is controlled by a muscular sling which controls the anorectal angle, between an acute angle (closed) and an obtuse angle (open). Lack of proper control can lead to constipation or faecal incontinence. In addition to anorectal angle, the manometric pressure at various points in the rectum and anal canal may be detected, and electro-myological readings may be taken to determine muscle activity.

Deen performed by inserting into the rectum of the patient a radiological contrast medium which has the consistency of a soft stool, to simulate a soft faecal motion. The patient then sits on a radiolucent toilet and is screened radiologically whilst defecating. The difference between the angle of the rectum before and during defecation provides some indication as to whether there may be a functional disorder of the anorectum in patients who have

10

15

20

problems in defecating. This procedure is referred to as a defecating proctogram and is unpleasant for the patient, invasive (requiring exposure to radiation) and many Radiological Units will not or cannot perform the procedure. The procedure also of course requires special equipment and a skilled radiologist to observe and interpret the results.

A need therefore exists for an apparatus and method for use in monitoring the anal canal and/or rectum, for example for measuring anorectal angle which, alleviates at least some of the above problems, allowing the measurement to be carried out more widely.

Accordingly, in one aspect, this invention provides a method for use in monitoring the anal canal and/or rectum of a patient, which comprises inserting through the anus into the rectum an elongate flexible element and measuring or observing the angular deflection of said flexible element, and/or the contour adopted thereby.

Preferably, said angular deflection is measured in a single plane, for example the horizontal plane if the patient is lying on his or her side.

Preferably the change of said angular deflection is measured during a simulated defecatory process.

Preferably, said angular deflection is measured using a sensor associated with said elongate flexible element.

Thus in preferred embodiments of this invention, the anorectal angle may be measured without requiring exposure to radiation and without requiring the patient to defecate.

In another aspect, this invention provides apparatus

10

15

20

25

for use in monitoring the anal canal and/or rectum of a patient, which apparatus comprises an elongate flexible element designed to be introduced <u>via</u> the anus into the rectum and having associated therewith angular deflection detecting means for detecting the angular deflection thereof and/or the contour adopted by said flexible element.

Preferably, said angular deflection detecting means comprises an elongate flexible core element and sensor means responsive to longitudinal strain disposed along opposed sides of the core element to determine angular deflection between spaced regions thereof. In one embodiment, the sensor means comprise respective elongate strain gauges extending along substantially the whole length of the elongate flexible core element at circumferentially spaced locations.

Preferably said elongate flexible element comprises a rubber or rubber-like outer sheath within which is disposed said angular deflection detecting means.

Preferably, said outer sheath includes an inflatable region in the distal position thereof, and whereby said region may be inflated in use to stimulate the rectum.

Preferably, said apparatus includes pressure detecting means for determining in use the pressure acting in the rectum or adjacent the anus. The pressure detecting means may comprise one or more pressure sensors located in the outer sheath or pressure ports disposed in the outer sheath leading to one or more associated sensors.

In this way, a single instrument may be provided which

provides a reading of anorectal angle and manometric pressure, and so a 3-D pressure map of pressures within the anorectal region may be constructed.

In a further aspect, this invention provides use of the apparatus as defined as a bio-feedback sensor for training patients with defecatory disorders.

Whilst the invention has been described above, it extends to any inventive combination of features set out above or in the following description.

The invention may be performed in a various ways and an embodiment thereof will now be described in detail, reference being made to the accompanying drawings in which:-

Figure 1 is a schematic side view of apparatus in accordance with this invention;

Figure 2 is a cross sectional view on an enlarged scale of the apparatus of Figure 1, and

Figure 3 is a schematic view showing the apparatus in use.

- The apparatus 10 for measuring anorectal angle comprises an outer rubber-like sheath 12, which may be a suitably modified catheter, within which is disposed an elongate angular deflection detector 14 which provides on display 16 a read-out of the angular deflection of the apparatus.
- Referring to Figures 1 and 2, the angular deflection detector 14 comprises an anchorage or "fixed" end 17 from which extends a core element 18 of flexible wire or cable and four strain gauge wires 20 extending along the length of

WO 97/10746 PCT/GB96/02296

5

the core and equispaced at 90° around the core, the whole being covered in thin plastics cover 21 (see Figure 2). Such a detector is obtainable from Penny and Giles Limited, Blackwood, Gwent, U.K.

The strains experienced by the strain gauge wires 20 are calculated to determine the total strain acting along the whole core on all four sides, thereby to determine the angular deflection between the tip 22 and the anchorage 17. In this particular example, only deflections in the plane of the section shown in Figure 3 are monitored. The apparatus 10 includes a mark 24 on the outer sheath to ensure that the instrument is used in the correct orientation. Also, as the accuracy of this particular sensor will be degraded if the angular deflection detector 14 is twisted, the apparatus includes thin flexible strips 26 to either side of the 15 detector to ensure that flexing of the apparatus is confined to the single plane only. From the anchorage 17 the signals are fed by a cable 28 to a processor 30 which drives the display 16. The output is also available to interface with a suitable PC/software package (not shown) to allow the 20 output from the instrument to sampled, correlated and/or combined with data from the other sensors for further processing as required.

The outer sheath 12 has a central bore in which the
deflection detector 14 and strips 26 are snugly located, and
the sheath 12 is bonded to the detector anchorage 17. The
sheath induces an inflatable balloon chamber 31 at its
distal end, fed by a line 32 which runs back to the proximal

15

20

end of the device. Likewise eight pressure sample points 34 are located along the extension of the sheath and respective passages run back to the distal end.

In use, the apparatus is inserted into the anus of a patient with the mark 24 aligned with the anterior plane of the patient and pushed in until the distal end is well into the patient's rectum, as seen in Figure 3. Measurements of angle and pressure may been be taken. The balloon 31 may be inflated to stimulate defectation or the patient may be asked to push, and the corresponding change in angle measured.

The apparatus gives a quick read out which does not require interpretation to determine the actual angle, and so a numerical score can be given easily. There is minimal invasion of patient privacy compared to the defecating proctogram.

The apparatus is especially suited to bio-feedback, as a patient may be given the apparatus and instructed to practice regularly to obtain a particular angle on the display. In this way, the patient may relearn the appropriate response which may have been lost previously.

CLAIMS


- 1. A method for use in monitoring the anal canal and/or rectum of a patient, which method comprises inserting through the anus into the rectum an elongate flexible element and measuring or observing the angular deflection of said flexible element and/or the contour adopted thereby.
- 2. A method according to Claim 1, wherein said angular deflection is measured in a single plane.
- A method according to Claim 1 or Claim 2, wherein the
 change of said angular deflection is measured during a simulated defacatory process.
 - 4. A method according to any preceding Claim wherein said angular deflection is measured using a sensor associated with said elongate flexible element.
- 5. A method according to any preceding Claim, which further includes monitoring the pressure at one or more points in the anal canal and/or rectum using one or more sensor means provided on said elongate flexible element.
- 6. Apparatus for use in monitoring the anal canal or
 20 rectum of a patient, which apparatus comprises an elongate
 flexible element designed to be introduced via the anus into
 the rectum and having associated therewith angular
 deflection detecting means for detecting angular deflection
 thereof.
- 7. Apparatus according to Claim 6, wherein said angular deflection detecting means comprises an elongate flexible core element and sensor means responsive to longitudinal

10

strain along opposed sides of the core element to determine angular deflection between spaced regions thereof.

- 8. Apparatus according to Claim 7, wherein the sensor means comprise respective elongate strain gauges extending along substantially the whole length of the elongate flexible core element at radially spaced locations.
- 9. Apparatus according to any of Claims 6 to 8, wherein said elongate flexible element comprises a rubber or rubber-like outer sheath within which is disposed said angular deflection detecting means.
- 10. Apparatus according to any of Claims 6 to 9, wherein said outer sheath includes an inflatable region in the distal position thereof, and whereby said region may be inflated in use to stimulate the rectum.
- 15 11. Apparatus according to any of Claims 6 to 10, wherein said apparatus includes pressure detecting means for determining in use the pressure acting in the rectum or adjacent the anus.
- detecting means comprises one or more pressure sensors located in the outer sheath or pressure ports disposed in the outer sheath leading to one or more associated sensors.

 13. A bio-feedback sensor for training a patient with a defacatory disorder, including an elongate flexible element designed to be introduced via the anus into the rectum and having associated therewith angular deflection detecting means for detecting angular deflection thereof.



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

Inten. Al Application No PCT/GB 96/02296

	<u> </u>			
A. CLASSI	IFICATION OF SUBJECT MATTER A61B5/03 A63B23/20			
According t	to International Patent Classification (IPC) or to both national classi-	fication and IPC		
	S SEARCHED	rice embols		
IPC 6	documentation searched (classification system followed by classification s	ion symbots)		
		•	•	
Documenta	tion searched other than minimum documentation to the extent that	such documents are included in the fields se	arched	
		,		
Electronic o	data base consulted during the international search (name of data ba	se and, where practical, search terms used)		
	•			
C. DOCUM	MENTS CONSIDERED TO BE RELEVANT			
Category *	Citation of document, with indication, where appropriate, of the i	elevant passages	Relevant to claim No.	
	c			
Α	US,A,4 687 002 (C.J.LAHR) 18 Aug		1,6	
	see column 3, line 61 - column 6 tables 1-6	, THIE 57;	•	
Α	US,A,4 873 990 (H.K.HOLMES ET AL October 1989) 1/	1,8	
	see column 4. line 58 - column 5	, line 26	•	
	see column 4, line 15 - line 23;	tables		
	1-5	·		
A	US,A,4 366 810 (C.A.SLANETZ,JR)	5,11,12		
	1983 see column 6, line 64 - column 8	line 15.		
	tables 5-7	,		
ŀ				
		·		
	<u> </u>			
Fur	ther documents are listed in the continuation of box C.	Patent family members are listed	in annex.	
* Special c	ategories of cited documents:	T later document published after the inte	emational filing date	
'A' docum	ment defining the general state of the art which is not dered to be of particular relevance	or priority date and not in conflict we cited to understand the principle or th		
'E' carlier	r document but published on or after the international clate	invention "X" document of particular relevance; the		
'L' docum	nent which may throw doubts on priority claim(s) or h is cited to establish the publication date of another	cannot be considered novel or cannot involve an inventive step when the do	cument is taken alone	
citati	on or other special reason (as specified) ment referring to an oral disclosure, use, exhibition or	"Y" document of particular relevance; the cannot be considered to involve an in document is combined with one or m	ventive step when the	
other	means ment published prior to the international filing date but	ments, such combination being obvious to the art.		
	than the priority date claimed	*&* document member of the same patent family		
Date of the	e actual completion of the international search	Date of mailing of the international se	arch report	
	2 December 1996	21. 01. 97		
Name and	I mailing address of the ISA	Authorized officer		
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Ruswijk			
1	Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Weihs, J		

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter nal Application No PCT/GB 96/02296

Patent document cited in search report	Publication date	Patent memb		Publication date
US-A-4687002	18-08-87	US-A- US-A-	4739767 5005586	26-04-88 09-04-91
US-A-4873990	17-10-89	NONE		
US-A-4366810	04-01-83	US-A-	4469091	04-09-84

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked.

☐ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.